



## SMEG UNDERCOUNTER COMMERCIAL DISHWASHER

### DIMENSIONS:

Height: 820mm  
Width: 600mm  
Depth: 600mm

### SUITABLE FOR:



HOUSING  
ASSOCIATIONS



HEALTHCARE



HOTELS &  
HOSPITALITY

### FEATURES:

- ▶ Double skinned construction
- ▶ Double basket capability
- ▶ Electronic soft touch controls
- ▶ WRAS approved
- ▶ Auto-dosing chemical
- ▶ Wash pump with "soft start"
- ▶ Thermostop controlled rinse temperature
- ▶ Insulated boiler
- ▶ Auto-start function via door closure
- ▶ Atmospheric boiler and rinse pump (HTR)

- ▶ Door opening system
- ▶ Planetarium washing system
- ▶ Natural condenser drying
- ▶ Adjustable feet

### OPTIONS:

- ▶ Dry Assist +
- ▶ Delay timer option
- ▶ 1/2 load FlexiZone

**ONECARE<sup>∞</sup>** This machine is eligible for our all inclusive service solution, One Care.

**SMEG UNDERCOUNTER SPECIFICATIONS**

Cycle time	min	1
Baskets (x2)	mm	500 x 500
Height	mm	820
Width	mm	600
Depth	mm	600
Baskets per hour		120 / 80 / 48 / 40
Number of programmes		7
Thermo-acoustic insulation		Door and wash chamber
Rinse aid dispenser		Peristaltic pump with electronic adjustment
Detergent dispenser		Peristaltic pump with electronic adjustment
Wash tank capacity	lts	11
Boiler capacity		6
Boiler element	kg	5kW 1ph / 5kW 3ph / 3.3kW 1ph / 1.7kW 1ph
Wash tank heating element	kW	2.0
Power supply / Total power installed		1ph 5.7kW 25A / 3ph 5.7kW 16A / 1ph 4kW 20A / 1ph 2.7kW 13A
Wash pump	kW	0.7
Water consumption per cycle	lts	2.7
Weight (net/gross)	kg	68/76
Adjustable feet		Yes
Water connection		3/4" BSP
Useable loading height	mm	415
Inlet water max temperature	°C	60