

SCHULTHESS STARLINE 7720



DIMENSIONS: CAPACITY:

Height: 850mm Width: 600mm Depth: 670mm

7kg

SUITABLE FOR:





ASSOCIATIONS

FEATURES:

- Large 4.3" colour display
- Drum vanes for 3D-Washing
- LED drum lighting
- Drum capacity: 60 I
- Spin speed: 1500 rpm
- G Factor 605
- Residual moisture 44%
- Door opening angle 180°
- Programme progress and remaining time display
- ▶ 24 freely programmable slots

- profiClean programme button
- Favorites for your 6 favourite programmes
- ▶ 35 profiClean programmes for small commercial businesses, building cleaners and special programmes
- ▶ 40-85 °C disinfection programmes Programme groups Sportswear, Businesswear, Home care, Antibac

OPTIONS:

- Hot water connection
- Programme expansion module with PC interface
- Coin box interface
- Machine plinth in chrome steel, H: 35.5 cm
- Machine plinth with fluff filter drawer, H: 40 cm
- Drain valve or drain pump Door hinge right or left

ONECARE[®]

This machine is eligible for our all inclusive service solution, One Care.



This machine is compatible with our smart laundry solution, serviceMaster



SCHULTHESS

STARLINE 7730



DIMENSIONS: CAPACITY:

Height: 850mm 7kg

Width: 600mm Depth: 640mm

SUITABLE FOR:





FEATURES:

- Condensation dryer
- Large 4.3" colour display
- > Stainless steel drum
- LED drum lighting
- Drum capacity: 118 l
- Electronically and time controlled drying programmes
- Residual moisture measurement
- Language selection button
- Excellent noise insulation
- Crease protection
- Programme progress and
- Door opening angle 180° remaining time display

OPTIONS:

- Door hinge right or left
- Machine plinth in chrome steel, H: 35,5 cm
- Stacking kit for washer-dryer tower
- Coin box interface

This machine is eligible for our all inclusive service solution, One Care.



This machine is compatible with our smart laundry solution, serviceMaster

STARLINE 7720 WASHING MACHINE	
Model with drain pump (P)	7720.1PU
Model with drain valve (V)	7720.1UV
Application features	
Load capacity	7kg
Drum capacity	601
Spinning speed	1500 rpm
g Factor	605g
Residual moisture ¹⁾	44%
Structural design	
Footed appliance with	
work surface	•
Door hinge ³⁾	r/l/w
Dimensions	
Height Width	85cm 60cm
Depth including distance	
from wall	67cm
Depth with door open (front loader)	110cm
Height (adjustable)	1cm
Weight when empty	90kg
Equipment	
Detergent tank and drum	chrome-nickel steel
Loading opening	34cm / 180°
Automatic door opening	•
Connecting cable	1.6m
Drain:	
- Drain hose with benda, only model (P)	1.5m
- Model with drain pump (P)	21mm
- Model with drain valve (V)	50mm
Electric power and water s	upply
Electrical connection	400 V 2N~ / 50Hz / 4.6kW 10A
Voltage / connected loads /fuse	230 V 1 N~ / 50Hz / 2.3kW 10A
Water connection	
- Pressure hose G ¾" with fine filter	1.5m
- Can be connected to cold water hot water	cold water/ hot water 70°C
- Water pressure	1-10 bar
Safety and service	
Conforms to the European Machinery Directive	2006/42/EC
Country of origin	Switzerland
Guarantee	1 year
Service by	Schulthess Maschinen AG

Product number	7730.1U
Application features	7730.10
Load capacity	7kg
Structural design	, N. 9
Footed appliance with	
work surface	•
Standard unit for wash	
and dry column Door hinge ³⁾	r/l/w
Dimensions	.,,,,
Height	85cm
Width	60cm
Depth including distance from wall	64cm
Height for built-in installation	85.5cm
Depth with door open	122cm
Height adjustable	2cm
Drying control	
By time selection 5)	•
Automatic by electronic moisture detection 6)	
System and equipment	
Drying technology	Air condensation system
Programme time display	•
Load quantity display	•
Automatic door opening	•
Loading opening	vorne, x 36 / 31cm / 180°
LED drum lighting	
Connecting cable	1,5m
Outlet hose	2m / x 22 mm
Condensate drainage	
in container / Drainage direct	•
Exhaust line	-
Maximum drainage height	1m
Exhaust hose x 100 mm	-
Power supply	
Electrical connection 7)	
Voltage	400 V 2N~ / 230 V 1N~
Connected values	2,8 / 2,1 kW
Fuse protection	10 / 10 AT
	- Machine plinth
	– Machine plinth with drawer for fluff filter
Safety and service	
Conforms to the European Machinery Directive	2006/42/EC
Country of origin	Switzerland
Guarantee	1 year
Service by	Schulthess Maschinen AG
•	
Name and address of	Schulthess Maschinen AG