

SCHULTHESS TOPLINE 9240



DIMENSIONS: CAPACITY:

Height: 900mm 7kg Width: 630mm

Depth: 720mm

SUITABLE FOR:





FEATURES:

- Large 4.3" colour display
- Drum vanes for 3D-Washing
- Drum capacity: 70 l
- Spin speed: 1600 rpm
- G Factor 690
- Residual moisture 43%
- Language selection button
- (23 languages)

- profiClean programme button
- USB-interface for PC software
- Drain valve or drain pump
- 94 profiClean and 24 freely programmable slots

OPTIONS:

- Drain valve or drain pump
- Anthracite or chrome steel finish
- Door hinge right or left
- Liquid detergent pumps

○ NECARE [∞] This machine is eligible for our all inclusive service solution, One Care.



This machine is compatible with our smart laundry solution, serviceMaster



SCHULTHESS

TOPLINE



MODELS: DIMENSIONS: CAPACITY:

TA 9340 HxWxD: 900x630x830mm 8kg TC 9350 HxWxD: 900x630x840mm

TW 9360 HxWxD: 900x630x840mm

SUITABLE FOR:

- M COMMERCIAL LAUNDRIES 😂 SCHOOLS & EDUCATION
- → HEALTHCARE

 ✓ LAUNDRETTES

 ✓ VETS & EQUINE

FEATURES:

- Load capacity: 8 kg
- Large 4.3" colour display
- Drum capacity: 150 l
- LED drum lighting
- Residual moisture measurement
- Language selection button
- Electronically and time controlled drying programmes

OPTIONS:

- Exhaust air system (TA 9340)
- Condensation system (TC 9350) Condensation system with heat
- pump (TW 9360) Anthractite or chrome steel finish
- Door hinge right or left

○ NECARE [©] This machine is eligible for our all inclusive service solution, One Care.



This machine is compatible with our smart laundry solution, serviceMaster

STARLINE 7720	WASHING MACHINE
Model with drain pump (P)	7720.1PU
Model with drain valve (V)	7720.1UV
Application features	
Load capacity	7kg
Drum capacity	601
Spinning speed	1500 rpm
g Factor	605g
Residual moisture ¹⁾	44%
Structural design	
Footed appliance with	
work surface	•
Door hinge ³⁾	r/l/w
Dimensions	
Height Width	85cm 60cm
Depth including distance	
from wall	67cm
Depth with door open (front loader)	110cm
Height (adjustable)	1cm
Weight when empty	90kg
Equipment	
Detergent tank and drum	chrome-nickel steel
Loading opening	34cm / 180°
Automatic door opening	•
Connecting cable	1.6m
Drain:	
- Drain hose with benda, only model (P)	1.5m
- Model with drain pump (P)	21mm
- Model with drain valve (V)	50mm
Electric power and water supply	
Electrical connection	400 V 2N~ / 50Hz / 4.6kW 10A
Voltage / connected loads /fuse	230 V 1 N~ / 50Hz / 2.3kW 10A
Water connection	
- Pressure hose G ¾" with fine filter	1.5m
- Can be connected to cold water hot water	cold water/ hot water 70°C
- Water pressure	1-10 bar
Safety and service	
Conforms to the European Machinery Directive	2006/42/EC
Country of origin	Switzerland
Guarantee	1 year
Service by	Schulthess Maschinen AG

TOPLINE PRO 9240		
Model with drain pump (P)	9240.1EPU	
Model with drain valve (V)	9240.1EUV	
Application features		
Load capacity	8kg	
Drum capacity		
Spinning speed	•	
g factor	•	
Residual moisture 1)	r/l/w	
Structural design		
Footed appliance with work surface	•	
Door hinge 2)	r/l/w	
Dimensions		
Height	90cm	
Width	63cm	
Depth including distance from wall	72cm	
Depth with door open (front loader)	116cm	
Height (adjustable)	1cm	
Weight when empty	102kg	
Equipment		
Detergent tank and drum	chrome-nickel steel	
Loading opening	34 / 180°	
Automatic door opening	•	
Connecting cable	1,6cm	
Drain		
- Drain hose with benda, only model (P)	1,5m	
Model with drain pump (P)	21mm	
Model with drain valve (V)	50mm	
Electric power and water supply		
Voltage / connected loads / fuse	400 V 3 N~ / 50Hz / 4,6kW / 10A 400 V 2 N~ / 50Hz / 4,6kW / 10A 230 V 1 N~ / 50Hz / 2,5kW / 13A 230 V 1 N~ / 50Hz / 2,3kW / 10A	
Water connection		
Pressure hose G ¾" with fine filter	1,5m	
Can be connected to cold water / hot water	cold water / hot water 70 °C	
Water pressure	1–10 bar	
Safety and service		
Conforms to the European Machinery Directive	2006/42/EC	
Country of origin	Switzerland	
Guarantee	1 year	
Service by	Schulthess Maschinen AG	
Name and address of supplier	Schulthess Maschinen AG, CH-8633 Wolfhausen/ZH	