



MAIDAID C RANGE UNDERCOUNTER

MODELS:

C612
C615 ws
C652
C525 ws
C512D
C512

DIMENSIONS:

HxWxD: 840x580x700mm
HxWxD: 840x580x700mm
HxWxD: 1100x580x700mm
HxWxD: 810x580x610mm
HxWxD: 810x580x610mm
HxWxD: 810x580x610mm

SUITABLE FOR:



FEATURES:

- ▶ Four button bright LED line display with soft touch controls, twin traffic lights giving instant status updates & operational self-diagnostics.
- ▶ Alarm menu with hi-level information retrieval
- ▶ Rinse arm design
- ▶ Three standard cycle time options with further options available
- ▶ Selectable energy saving mode
- ▶ Selectable thermostop ensures optimum rinse temperatures
- ▶ Patented dual flow wash pump; reducing power consumption whilst retaining wash efficiency
- ▶ Moulded wash tank for easy cleaning
- ▶ Moulded rack guide giving partial double skin
- ▶ Accurate detergent & rinse aid peristaltic dosing pump as standard

MODEL SPECIFICS:

- ▶ Stainless steel surface scrap tray filters supplied as standard (C612, C615 WS, C652)
- ▶ Quick release triple wash (C612, C615 WS, C652)
- ▶ Quick release parallel wash (C525 WS, C512D, C512)
- ▶ Automatic continuous internal water softener (C525 WS, C615 WS)
- ▶ Substantial usable height of 375mm to cater for large wash ware (C612, C615 WS, C652)

ONECARE[∞] This machine is eligible for our all inclusive service solution, One Care.

		C612 + C615 ws + C652			C525 ws + C512D + C512			
Dimensions	mm	C612: 840x580x700 + Feet C615 ws: 840x580x700 + Feet C652: 1100x580x700 + Feet			C525 ws: 810x580x610 + Feet C512D: 810x580x610 + Feet C512: 810x580x610 + Feet			
Feet Height	mm	10-20			10-20			
Rack Size	mm	500x600			500x500			
Maximum usable height	mm	375			340			
Door opening	mm	405			365			
Theoretical productivity	Racks/h	40			51			
Effective productivity	Racks/h	30			36			
Wash tank element	kW	2.1			2.1			
Boiler element	kW	6			6			
Wash pump	kW	0.61			0.47			
Tank capacity	L	23			20			
Noise emission	dB	<55			<55			
Installed Power	AMP	kW	230V - 50Hz - 1N	13	2.8	230V - 50Hz - 1N	13	2.6
				20	4.7		20	4.5
				30	6.7		30	6.5
Optional 3 Phase config	kW	6.7			6.5			
Fused	amp	16			16			
Inlet water pressure	Bar	2 to 4			2 to 4			
Flow rate L/Min	L/Min	6			6			
Water inlet temp	°C	10 to 50			10 to 50			
Water connection	BSP	3/4			3/4			
Waste connection	Ø	Int 19/ext 24			C525 ws + C512D: Int 19/ext 24 C512: Int 29/ext 34			
Water consumption per cycle	L	2.5			2.0			
Wash temperature	°C	60 - adjustable			60 - adjustable			
Rinse temperature	°C	82 - adjustable			82 - adjustable			