

SCHULTHESS E2 IRONER RANGE



| MODEL: | DIMENSIONS: |
|--------|------------------|
| G14.25 | 1.4 Metre x 25cm |
| G15.35 | 1.5 Metre x 35cm |
| G18.35 | 1.8 Metre x 35cm |
| G21.35 | 2.1 Metre x 35cm |
| G21.50 | 2.1 Metre x 50cm |
| G26.35 | 2.6 Metre x 50cm |
| G26.50 | 2.6 Metre x 50cm |
| G32.50 | 3.2 Metre x 50cm |

SUITABLE FOR:

 [Call us for more info](#)

FEATURES:

- ▶ **Unmatched Finish:**
Achieve smooth results with a specially developed pressure roller. Get gentle care for delicate fabrics with Meta Aramid detaching linen ribbons.
- ▶ **Double Temperature:**
Top temperature control system with dual sensors. Exclusive mechanism prevents fluctuations, halts heating to protect textiles, and reduce energy waste.
- ▶ **Maintenance-Free:**
Padding-free rollers eliminate downtime from rubber peeling.
- ▶ **Strongly Built:**
Robust construction for long-term reliability, with oversized components and premium materials
- ▶ **Mirror Polished Cylinder:**
Seamless cylinders, ensuring optimal ironing results with mirror polishing for a smooth finish.
- ▶ **Patented Titanium-Steel Burner:**
Efficient burner for precise temperature control, boasting easy installation, servicing, and high reliability due to its patented design.
- ▶ **User-Friendly Control Panel**
A user-friendly interface allows personalised features, with smart diagnostics.
- ▶ **Easy Access to Components**
Components are easily accessible for inspection, ensuring smooth maintenance procedures.
- ▶ **Foot Pedal**
Stops roller rotation, leaving hands free to adjust linen during the feeding process.
- ▶ **Steam Extraction**
Air-Blades system provides extra-efficient steam extraction, reducing maintenance frequency.

SKS System efficiently collects steam flow, minimizing heat dispersion and shortening drying times.

ONECARE[∞] This machine is eligible for our all inclusive service solution, One Care.

| | | | G14.25 | G15.35 | G18.35 | G21.35 | G26.35 |
|---|-----------------------------|-------|-------------------------------|-------------------------------|-------------------------------|-------------------------------|-------------------------------|
| Cylinder Dimensions | | mm | 1450 x Ø270 | 1480 x Ø325 | 1800 x Ø325 | 2100 x Ø325 | 2580 x Ø325 |
| Supply Tension *, Electric/Gas/Steam | | | V.400/3N/50Hz V.230/1/50Hz | V.400/3N/50Hz V.230/1/50Hz | V.400/3N/50Hz V.230/1/50Hz | V.400/3N/50Hz V.230/1/50Hz | V.400/3N/50Hz V.230/1/50Hz |
| HEATING SOURCE | | | | | | | |
| Electric | Heating power | kW | 12 | 18 | 20,7 | 23,4 | 29,7 |
| Gas | Thermal power | kW | 13,6 | 22 | 25,6 | 27 | 33,5 |
| | Gas Consumption Nat. Gas | m³/h | 1,44 | 2,26 | 2,71 | 2,82 | 3,53 |
| | Gas Consumption LPG | kg/h | 1,05 | 1,8 | 2,02 | 2,2 | 2,5 |
| Steam | Average Consumption | kg/h | n/a | 18 | 22 | 26 | 32 |
| MOTOR(S) | | | | | | | |
| Electric/Steam | | kW | 0,27 | 1 | 1 | 1 | 1 |
| Gas | | kW | 0,32 | 1,2 | 1,2 | 1,2 | 1,2 |
| TOTAL POWER | | | | | | | |
| | Electric | A | V.400/3: 17,8 A | V.400/3: 29 A | V.400/3: 31,5 A | V.400/3: 38 A | V.400/3: 43 A |
| | Gas/Steam | A | V.230/1: 2,2 A | V.230/1: 5 A | V.230/1: 5 A | V.230/1: 5 A | V.230/1: 5 A |
| Ironing Speed, Variable | | m/min | 0,8 3 | 1,6 5 | 1,6 5 | 1,6 5 | 1,6 5 |
| Steam Extraction | | m³/h | 280 | 280 | 280 | 280 | 280 |
| Fumes Extraction | | m³/h | 100 | 140 | 140 | 140 | 140 |
| Hourly Production (Recommended Moisture 50%) | | kg | 25 | 43 | 50 | 56 | 75 |
| Ironer Dimensions | | mm | 2010x510x1080 | 2010x550x1100 | 2340x550x1100 | 2640x550x1100 | 3140x580x1150 |
| Packing Dimensions (W,D,H) | | mm | 2130x690x1300 | 2140x730x1560 | 2490x730x1560 | 2890x730x1560 | 3290x730x1560 |
| Weight, Gross/Net | | kg | 360/310 | 497/450 | 540/490 | 602/548 | 700/635 |

* DIFFERENT VOLTAGES AVAILABLE ON REQUEST, PLEASE CONTACT OUR SALES TEAM FOR MORE INFORMATION

| | | | G21.50 | G26.50 | G32.50 |
|---|-----------------------------|----------------------|--|--|---|
| Cylinder Dimensions | | mm | 2100 x Ø500 | 2580 x Ø500 | 3200 x Ø500 |
| Supply Tension * | | | V.400/3N/50Hz | 400/3N/50Hz | V.400/3N/50Hz |
| HEATING SOURCE | | | | | |
| Electric | Heating Power | kW | 45 | 57 | 66 |
| Gas | Thermal Power | kW | 54 | 67 | 95,2 |
| | Gas Consumption Nat. Gas | m³/h | 5,7 | 7 | 10 |
| | Gas Consumption LPG | kg/h | 4,3 | 5,3 | 7,5 |
| Steam | Average Consumption | kg/h | 50 | 70 | 90 |
| MOTOR(S) | | | | | |
| Electric/Steam | | kW | 1,6 | 1,6 | 1,6 |
| Gas | | kW | 2,7 | 2,7 | 2,7 |
| TOTAL POWER | | | | | |
| | Electric | A | 69 | 85 | 98 |
| | Gas/Steam | A | 5 | 5 | 5 |
| Ironing Speed, Variable | | m/min | 1,6 8 | 1,6 8 | 1,6 8 |
| Steam Extraction | | m³/h | 740 | 740 | 740 |
| Fumes Extraction | | m³/h | 1200 | 1200 | 1200 |
| Hourly Production (Recommended Moisture 50%) | | kg/h kg/h kg/h | 75 kg/h el 85 kg/h gas 95 kg/h steam @4bar | 95 kg/h el 110 kg/h gas 115 kg/h steam @4bar | 120 kg/h el 135 kg/h gas 145 kg/h steam @4bar |
| Ironer Dimensions | | mm | 2880x750x1290 | 3280x750x1290 | 3880x750x1290 |
| Packing Dimensions (W,D,H) | | mm | 2990x920x1600 | 3390x920x1600 | 4190x920x1600 |
| Weight, Gross/Net | | kg | 1288/1200 | 1413/1320 | 1800/1700 |

* DIFFERENT VOLTAGES AVAILABLE ON REQUEST, PLEASE CONTACT OUR SALES TEAM FOR MORE INFORMATION