



SCHULTHESS STARLINE 7720

DIMENSIONS:

Height: 850mm
Width: 600mm
Depth: 670mm

CAPACITY:

7kg

SUITABLE FOR:



HOUSING
ASSOCIATIONS



HEALTHCARE

FEATURES:

- ▶ Large 4.3" colour display
- ▶ Drum vanes for 3D-Washing
- ▶ LED drum lighting
- ▶ Drum capacity: 60 l
- ▶ Spin speed: 1500 rpm
- ▶ G Factor 605
- ▶ Residual moisture 44%
- ▶ Door opening angle 180°
- ▶ Programme progress and remaining time display
- ▶ 24 freely programmable slots
- ▶ profiClean programme button
- ▶ Favorites for your 6 favourite programmes
- ▶ 35 profiClean programmes for small commercial businesses, building cleaners and special programmes
- ▶ 40–85 °C disinfection programmes Programme groups Sportswear, Businesswear, Home care, Antibac

OPTIONS:

- ▶ Hot water connection
- ▶ Programme expansion module with PC interface
- ▶ Coin box interface
- ▶ Machine plinth in chrome steel, H: 35.5 cm
- ▶ Machine plinth with fluff filter drawer, H: 40 cm
- ▶ Drain valve or drain pump
- ▶ Door hinge right or left

ONECARE[∞] This machine is eligible for our all inclusive service solution, One Care.

**service
Master** 

This machine is compatible with our smart laundry solution, serviceMaster

STARLINE 7720 WASHING MACHINE

Model with drain pump (P)	7720.1PU
Model with drain valve (V)	7720.1UV
Application features	
Load capacity	7kg
Drum capacity	60l
Spinning speed	1500 rpm
g Factor	605g
Residual moisture ¹⁾	44%
Structural design	
Footed appliance with work surface	•
Door hinge ³⁾	r/l/w
Dimensions	
Height	85cm
Width	60cm
Depth including distance from wall	67cm
Depth with door open (front loader)	110cm
Height (adjustable)	1cm
Weight when empty	90kg
Equipment	
Detergent tank and drum	chrome-nickel steel
Loading opening	34cm / 180°
Automatic door opening	•
Connecting cable	1.6m
Drain:	
– Drain hose with benda, only model (P)	1.5m
– Model with drain pump (P)	21mm
– Model with drain valve (V)	50mm
Electric power and water supply	
Electrical connection	400 V 2N~ / 50Hz / 4.6kW 10A
Voltage / connected loads /fuse	230 V 1N~ / 50Hz / 2.3kW 10A
Water connection	
– Pressure hose G ¾" with fine filter	1.5m
– Can be connected to cold water hot water	cold water/ hot water 70°C
– Water pressure	1-10 bar
Safety and service	
Conforms to the European Machinery Directive	2006/42/EC
Country of origin	Switzerland
Guarantee	1 year
Service by	Schulthess Maschinen AG